

STANDARD WOOL FELT⁺

For evaluations with rub fastness tester

Standard wool felt, white and black, for evaluations with rub fastness tester FEK-VESLIC.

For tests according to:

+ VESLIC C-4500

+ ISO 11640:2018

+ IUF 450

Article 701

Wool felt, white



Inspection Standard of article 701

Parameter	Art. 701 – specified value
Appearance	Square pieces of white* wool felt, measuring 15 mm x 15 mm, punched out of a sheet of pure wool felt
Weight	1900 g/m ² +/-150 g/m ²
Density	0.32 g/cm ³ -0.37 g/cm ³ (category F1, DIN 61200)
pH	4.0 – 8.0
Thickness	6.0 mm +/- 0.5 mm

* compared to a Standard-batch (internal method)

Article 702

Wool felt, black



Inspection Standard of article 702

Parameter	Art. 702 – specified value
Appearance	Square pieces of black* wool felt, measuring 15 mm X 15 mm, punched out of a sheet of pure wool felt
Weight	1900 g/m ² +/-150 g/m ²
Density	0.32 g/cm ³ -0.37 g/cm ³ (category F1, DIN 61200)
pH	4.0 – 8.0
Thickness	6.0 mm +/- 0.5 mm

* compared to a Standard-batch (internal method)

Available in packs:

701: 1000 pieces per pack

702: 100 pieces per pack